




| Referans Nr. |  | a h6    | b -0.6 | $\overset{c}{\text{DIN 650}}$ | d $\pm 0.01$ | h1 $\pm 0.01$ | h1 $\pm 0.02$ | h2 | h3 | ISO 4762<br> | <br>(g) |
|--------------|---|---------|--------|-------------------------------|--------------|---------------|---------------|----|----|---|--|
| 2120-1425    | 14  | 0-0.011 | 14     | 24                            | 32           | 25            | -             | 9  | 8  | M8x35   | 200  |
| 2120-1450    | 14  | 0-0.011 | 14     | 24                            | 32           | -             | 50            | 9  | 8  | M8x60   | 355  |
| 2120-1825    | 18  | 0-0.011 | 18     | 30                            | 40           | 25            | -             | 15 | 10 | M10x40  | 360  |
| 2120-1850    | 18  | 0-0.011 | 18     | 30                            | 40           | -             | 50            | 15 | 10 | M10x65  | 600  |
| 2120-2225    | 22  | 0-0.013 | 22     | 38                            | 40           | 25            | -             | 15 | 14 | M10x50  | 410  |
| 2120-2250    | 22  | 0-0.013 | 22     | 38                            | 40           | -             | 50            | 15 | 14 | M10x75  | 650  |

### Ürün Nr. 2120 Silindir Dayama

- Sertleştirilmiş
- Siyah Kaplama

### Product Nr. 2120 Cylinder Pluggable

- Hardened
- Black coating

