

Modell / Model		CD-2	CD-4	CD-6	CD-10	CD-16	CD-25
Spannkapazität Capacity of clamp	Ton	2	4	6	10	16	25
Total-Hub (X) Total stroke (X)	mm	8	8	8	8	8	8
Spannhub (Y) Stroke of clamp (Y)	mm	3	3	3	3	3	3
Schonhub (Z) Preserved stroke (Z)	mm	5	5	5	5	5	5
Zylinder-Gesamtvolumen Total volumn of cylinder	cc	7.5	13	21	38	55	98
Toleranzen Werkzeugunerteil-Dicke (H) The toleranace of the template thickness (H)	mm	±2	±2	±2	±2	±2	±2



Hydraulischer Druck / Hydraulic pressure : 250kgf/cm²

Referenz-Nr. Order No.	A	B	C	D	E min.	F	G	W	N max.	T
1015-CD02	12	20	80	98	90	76	30	124	25	M10x20D
1015-CD04	12	25	100	109	93	87	30	135	30	M12x24D
1015-CD06	15	30	120	126	109	104	30	152	35	M12x24D
1015-CD10	15	35	150	148	131	124	36	174	40	M14x28D
1015-CD16	20	40	200	166	142	138	44	200	50	M18x36D
1015-CD25	20	45	235	200	163	168	48	240	60	M22x45D

1015

- Temperatur Standard : 60°
- Temperatur Optional : 160°

1015

- Standard Temperature : 60°
- Optional Temperature : 160°

