

Referenz-Nr. Order No.		s1	m	sw	L	h	k	n	b	Spannkraft Clamping Force kgf	
2150-08	8	1.4	5	4	23	9.5	6	7.7	13	310	25
2150-10	10	1.4	5	4	23	14	6	9.7	15	310	35
2150-12	12	1.2	7	5	28	15	7	11.7	18	340	60
2150-14	14	1.7	7	7	30	22	8	13.7	22	800	95
2150-16	16	1.7	10	8	30	22	9	15.7	25	1500	130
2150-18	18	2	10	8	35	28	10	17.7	28	1500	190
2150-20	20	2.5	13	10	40	32	12	19.7	32	2000	290
2150-22	22	2.5	13	12	45	38	14	21.7	35	2000	390

2150

- Die T-Nut des Produkts tritt vollständig in die Nut der Tischplatte ein. Da nur der exzentrische Kopfstück auf der Tischoberfläche verbleibt, ist ein einfaches Spannen der dünnen Teile möglich.
- geeignet für T-Nut DIN 650
- Gehärtet
- Schwarz beschichtet

2150

- T-Slot of the product enters in the slot of the bench completely. Since only the eccentric headpiece remains on the surface of the table, this provides easy clampings of the thin pieces.
- It is in compliance with DIN 650 T-Slot
- Hardened
- Black coating

