

Model		CV-4	CV-6	CV-10
Capacity of clamp	Ton	4	6	10
Total stroke (X)	mm	8	8	8
Stroke of clamp (Y)	mm	4	4	4
Preserved stroke (Z)	mm	4	4	4
Total volumn of cylinder	cc	13	21	32
The tolerance of the template thickness (H)	mm	±2	±2	±2

Hydraulic pressure : 250kgf/cm2



Referans Nr.		A	B	C	D	E + K1	Adjustment Distance	F	Max. L	M	ØG	ØJ	K	P
1010-CV042020125	20	19.6	32	12	85	70	15	65	125	M20	20	58	15	PT 1/4
1010-CV042022160	20	19.6	32	12	110	70	40	65	160	M20	20	58	15	PT 1/4
1010-CV042020160	22	21.6	35	14	85	70	15	65	125	M20	20	58	15	PT 1/4
1010-CV042022125	22	21.6	35	14	110	70	40	65	160	M20	20	58	15	PT 1/4
1010-CV062424125	24	23.6	40	16	85	77	8	82	125	M24	24	64	15	PT 1/4
1010-CV062424160	24	23.6	40	16	110	77	33	82	160	M24	24	64	15	PT 1/4
1010-CV062428125	28	27.6	44	18	85	77	8	82	125	M24	24	64	15	PT 1/4
1010-CV062428160	28	27.6	44	18	110	77	33	82	160	M24	24	64	15	PT 1/4
1010-CV102727160	27	26.6	46	18	110	83	27	99	160	M27	27	78	15	PT 1/4
1010-CV102727200	27	26.6	46	18	125	83	42	99	200	M27	27	78	15	PT 1/4
1010-CV102732160	32	31.6	50	20	110	83	27	99	160	M27	27	78	15	PT 1/4
1010-CV102732200	32	31.6	50	20	125	83	42	99	200	M27	27	78	15	PT 1/4

Product Nr. 1010 Hydraulic Clamp Model CV

- Screw-distance adjustment can be made.

