


Model		CB-1	CB-2	CB-4	CB-6	CB-10	CB-16	CB-25
Capacity of clamp	Ton	1	2	4	6	10	16	25
Total stroke (X)	mm	6	8	8	8	8	8	8
Stroke of clamp (Y)	mm	2.5	3	3	3	3	3	3
Preserved stroke (Z)	mm	3.5	5	5	5	5	5	5
Total volumn of cylinder	cc	3	7.5	13	21	38	55	98
The tolerance of the template thickness (H)	mm	±1.5	±2	±2	±2	±2	±2	±2

Hydraulic pressure : 250kgf/cm2



- Please indicate the size of T-slot (a,b,c,d) and the thickness (H) of the template for the die when purchasing.

Referans Nr.	L	K	J	H min.	H+d min. max	E min.	F	G	a min.	C min.	P
1015-CB01	74.5	60	14.5	25	100	42	44	20	10	6.5	PT1/8
1015-CB02	110	90	20	25	100	73	68	32	14	10	PT1/4
1015-CB04	134	110	24	25	130	77	79	40	18	12	PT1/4
1015-CB06	159	130	29	30	150	92	96	46	22	14	PT1/4
1015-CB10	189	159	30	40	140	114	117	54	24	16	PT1/4
1015-CB16	230	200	30	40	130	126	129	58	28	20	PT1/4
1015-CB25	265	235	30	45	120	148	156	70	36	23	PT1/4


**Product Nr. 1015 Hydraulic Clamp Model CB**

- The sizes of clamps(A),(B),(C) and (D) are made based on the size of T-slot.

