

Referenz-Nr. Order No.	Betriebsdruck Operating Pressure	Arbeitstemperatur Operating Temperature	Spann-Typ Mounting Type	Hub Stroke (mm)	Bohrdurchmesser Diameter Ø (mm)	Kolbenstange Piston Rod Ø (mm)	Spannkraft Clamping Force (kg)	A	B	C	D	E	F	G	H	I	J	K	L	M	O	N	P	Q	R	R1	S	L1 Spannen / Clamp L2 Lösen / Unclamp	Gewicht Weight (kg)
1058-PLCU25	4-10 kgf/cm <sup>2</sup>	-10° ~ +80°	Kopfflansch & Einschraubzylinder Upper Flange & Threaded Body	22	Ø 25	Ø 14	27	128.5	86.5	25	61.5	50	17	16	M40 x1.5	60	50	37	18	23	23	7	35	25	5.5	9	M6 x1	M5 x0.8	0.60
1058-PLCU32				28	Ø 32	Ø 16	40	149.5	97.5	25	72.5	57	20	18	M50 x1.5	70	60	45	22	30	23	8	40	30	6.5	11	M8 x1.25	G 1/8	1.00
1058-PLCU40				30	Ø 40	Ø 16	66	157.5	97.5	25	72.5	60	25	20	M55 x1.5	75	65	50	24	32	26	10	42.5	32.5	6.5	11	M8 x1.25	G 1/8	1.20
1058-PLCU50				30	Ø 50	Ø 20	105	174	104	25	79	65	30	22	M65 x1.5	88	75	58	27.5	36	32	14	50.5	37.5	8.5	14	M12 x1.75	G 1/8	2.00
1058-PLCU63				30	Ø 63	Ø 20	166	179	105	25	80	69	30	22	M80 x1.5	108	90	70	32	42	35	14	63	45	8.5	14	M12 x1.75	G 1/8	2.70

1058



Mit Rohr / With Pipe

