


Referenz-Nr. Order No.	A	B	C	D	E	F	G (g6)	H	J (h6)	K	L	M	N	P (±0.02)	Q	R
1484-06501	65	57	10	47	39	70	28	12	6	5	19	M6	42	26	32	25
1484-09001	90	72	15	57	46	95	42	14	8	7	23	M8	60	36	38	28

Referenz-Nr. Order No.	T	U	V	W	Z	Spannkraft Clamping Force Kgf	Drehmoment Allowable Screw Torque (N - m)	 (kg)
1484-06501	15	18	4	M4	M8	400	60	1.1
1484-09001	17	22	6	M5	M10	600	100	2.6

1484

Technische Daten



- Teile-Wiederholgenauigkeit: ±0.03
- Spannbacken Wiederholgenauigkeit : ±0.02

Hinweis

- Ohne Werkstück nicht spannen.
- Bearbeiten nur so weit es zulässig ist.

Inhalt

- 1 St. Sicherungsring
- 1 St. Diamantnadel
- 1 St. Inbusmutter



1484

Technical Data

- Part locating repeatability: ±0.03
- Jaw locating repeatability: ±0.02

Notes

- Never tighten the locking screw without a part mounted, to avoid damage and deformation
- Do not machine the jaw deeper than allowed.

Included

- 1 of locking ring
- 1 of diamond pin
- 1 of socket-head cap screw

