


Ref.-Nr. Order No.	a	L	c/2	öffnen opens 2 x mm	b1	b2 ±0,02	p1	p2	s1	Spannkraft Clamping Force kgf	Drehmoment Allowable Screw Torque (N-m)	sw	 (kg)
2315-060	60	120	90	20	117.5	114.5	174	56	150	800	45	9	4.1
2315-078	78	180	130	30	159	155	224	73.5	200	1500	110	12	10
2315-100	100	220	154	38	159	155	274	95	250	1500	110	12	17.2



2315

- Dieses Produkt fixiert das zu bearbeitende Werkstück und führt gleichzeitig eine Zentrierung durch. Der Vorteil dieses Systems zeigt sich besonders bei der Bearbeitung von Materialien mit unterschiedlichen Außendurchmessern, da es diesen Prozess ohne Wechsel des Zentrums durchführt.
- Anwendungsbereiche: CNC Maschinen und 5-Achs Bearbeitungszentren
- Die gesamte Lauffläche ist fein geschliffen und gehärtet.
- Backen müssen separat bestellt werden.
- Schwarz beschichtet

2315

- This product fixes the material to be processes and at the same time it makes centering. The advantage of this system specially shows itself when making machinings of the materials having different outer diameter measurements as it implements this process without changing the center.
- Area of Using: This product is used in various industry machines such as CNC and CNC 5-Axis mechanical milling machines,
- Entire moving surface is sensitively grinded and hardened.
- You need to purchase jaws separate.
- Black coating

