





Referenz-Nr. Order No.	a	a1	b	c	k	L	d	e	h	i	n ±0.01	Spannkraft clamping force kgf	Bewegungsstrecke Moving Distance Torque	 (kg)
2370-051	130	188	60	58	135	327	64	209	160	-	105	1100	4	37
2370-052	130	185	140	63	225	400	69	300	160	173	105	2200	4	44
2370-053	160	201	200	63	300	485	93	353	166	170	105	3300	4	63
2370-054	200	240	250	63	360	530	93	410	166	185	105	4100	4	81

2370

- 6 bar
- Spannkraft 1100 - 4100 kg, einstellbar
- Verwendung: Fräsen CNC und mechanisch und sonstige Industriemaschinen
- Aktivflächen komplett feingeschliffen und feingehärtet

2370

- It works with 6 Bar Air. It provides speed in clamping-opening processes because of it's pneumatic structure.
- It fixes the workpiece with it's 1100 kgf and 4100 kgf clamping force. Clamping force can be adjusted with it arbitrary bar adjustment button.
- Area of Using: CNC and mechanical milling machines, drilling machines, various industrial machines
- Entire moving surface is sensitively grinded and hardened.



• Ersatzbacken sind nicht enthalten

• "k" measurement is reached by the spare jaws. The spare jaws are not included in the set.

2370-051 Detail

