

| Model                                                                              |     | CC-1 | CC-2 | CC-4 | CC-6 | CC-10 |
|------------------------------------------------------------------------------------|-----|------|------|------|------|-------|
| Bağlama kapasitesi<br>Capacity of clamp                                            | Ton | 1    | 2    | 4    | 6    | 10    |
| Toplam strok (X)<br>Total stroke (X)                                               | mm  | 9    | 9    | 9    | 12   | 12    |
| Pabuç strok (Y)<br>Stroke of clamp (Y)                                             | mm  | 4    | 4    | 4    | 4    | 4     |
| Muhafaza edilen strok (Z)<br>Preserved stroke (Z)                                  | mm  | 5    | 5    | 5    | 8    | 8     |
| Silindirin toplam hacmi<br>Total volumn of cylinder                                | cc  | 3    | 7.5  | 13   | 21   | 38    |
| Kalıp taban kalınlığı toleransı (H)<br>The tolerance of the template thickness (H) | mm  | ±1.5 | ±2   | ±2   | ±2   | ±2    |

Hidrolik basınç / Hydraulic pressure : 250kgf/cm<sup>2</sup>


- Satın almadan önce T-Kanal (a,b,c,d) ölçüsü ve kalıp tabanı kalınlığını (H) bildiriniz.
- Please indicate the size of T-slot (a,b,c,d) and the thickness (H) of the template for the die when purchasing.

| Referans Nr. | H<br>min. - max | A<br>min. | C<br>min. | E   | F    | G    | I     | J   | K  | L<br>min. | M    | T   | U   |
|--------------|-----------------|-----------|-----------|-----|------|------|-------|-----|----|-----------|------|-----|-----|
| 1015-CC01    | 20              | 10        | 6.5       | 43  | G+43 | H+9  | Ø16   | 75  | 33 | 27        | 21.5 | 1/8 | M5  |
| 1015-CC02    | 25              | 14        | 10        | 50  | G+50 | H+9  | Ø18   | 91  | 43 | 30        | 25   | 1/8 | M5  |
| 1015-CC04    | 25              | 18        | 12        | 65  | G+60 | H+9  | Ø30   | 115 | 55 | 40        | 32.5 | 1/8 | M8  |
| 1015-CC06    | 35              | 22        | 14        | 80  | G+65 | H+12 | Ø37.5 | 130 | 65 | 48        | 40   | 1/4 | M10 |
| 1015-CC10    | 40              | 24        | 16        | 100 | G+82 | H+12 | Ø50   | 160 | 85 | 60        | 49   | 1/4 | M12 |

**Ürün Nr. 1015 Hidrolik Pabuç Model CC**

- Pabuç ölçüleri (A),(B),(C) ve (D) T-Kanala bağlı olarak belirlenir.
- Standart Sıcaklık : 60°

**Product Nr. 1015 Hydraulic Clamp Model CC**

- The sizes of clamps(A),(B),(C) and (D) are made based on the size of T-slot.
- Standard Temperature : 60°

